

UP1000

ULTRAPAR

Specifications

Version 1.0 July 2003

ENGLISH



www.behringer.com



ULTRAPAR

Professional Die-Cast PAR Spotlight

- ▲ Extremely high luminous efficiency with low power consumption
- ▲ Ideally suited for BEHRINGER 575H lamp or compatible models with G9.5 socket (lamp not supplied, available as accessory)
- ▲ Ultra-rugged die-cast aluminum casing
- ▲ Four glass lenses included: narrow spot, spot and two medium flood
- ▲ Highly reflective polished reflector insert
- ▲ Color frame accepts standard color foils
- ▲ Compact dimensions for easy transport and handling
- ▲ Flexible mounting bracket allows precise positioning
- ▲ Designed in Germany. Manufactured under ISO9000 certified management system

SPECIFICATIONS

Power	575 W max. (120 V / 240 V)
Max. room temperature	$T_a = 45^{\circ}\text{C}$
Max. temperature of exterior surfaces	$T_{\text{max}} = 175^{\circ}\text{C}$
Dimensions (Height x Diameter)	approx. 11 3/4" (300 mm) x 9 1/4" (237 mm)
Weight	approx. 3.8 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without further notice. Specifications and appearance may differ from those listed or shown.

The information contained in this manual is subject to change without notice. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER is a registered trademark. ALL RIGHTS RESERVED.

© 2003 BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903